

Specifications

WindFree™ 1-Way Cassette

- 2-Step Cooling: Fast Cooling & WindFree™ Cooling.
- Blade angle between 37° and 87°, blade width 100 mm.
- Built-in humidity sensor.
- Height of only 135 mm.
- Built-in condensation drain pump (750 mmH₂O).



Indoor Unit		AJ026TNDKG/EU	AJ035TNDKG/EU
Capacity			
Cooling	kW	2.6	3.5
Heating @ +7 °C	kW	2.9	3.8
Performance			
Airflow Rate	m ³ /min	6.2/5.2/4.2	7.6/6.6/5.6
Sound Power	dB(A)	50	55
Sound Pressure	H/M/L	32/29/26	37/33/30
Electrical Data			
Power Source	Ø, #, V, Hz	1Ø, 2, 220-240 V, 50 Hz	1Ø, 2, 220-240 V, 50 Hz
Power Consumption	Cooling W	45	50
Heating W	W	45	50
Current Input	Cooling A	0.23	0.25
Heating A	A	0.23	0.25
Dimensions			
Net Dimensions (W x H x D)	mm	970 x 135 x 410	970 x 135 x 410
Net Weight	kg	10.0	10.0
Refrigerant			
Piping Connections	Liquid Pipe	Ø, inch	1/4
Gas Pipe	Ø, inch	3/8	3/8
Drain Pipe	Ø, mm	VP20 (OD 26, ID 20)	VP20 (OD 26, ID 20)
Others			
Panel	Model Code	PC1NWFMAN	PC1NWFMAN
Net Dimensions (W x H x D)	mm	1,198 x 135 x 500	1,198 x 135 x 500
Net Weight	kg	4.3	4.3
Accessories			
Drain Pump		Included	Included
Max. Lifting Height/Displacement	mm / litres/h	750/24	750/24


Accessories

Wireless Remote Controller	Advanced Wired Controller	Simple Type Controller	Touch Controller	Wi-Fi Kit	Panel (Required)
AR-EH03E	MWR-WG00JN/ MWR-WG00KN	MWR-SH00N	MWR-SH11N	MM-WI04EN	PC1NWFMAN

Dimensional drawings

WindFree™ 1-Way Cassette

AJ026TNDKG/EU



NO	Name	Description
1	Gas pipe connection	Ø12.70 (1/2)
2	Liquid pipe connection	Ø6.35 (1/4)
3	Drain hose connection	VP20 (OD 26, ID 20)
4	Power supply/communication wiring conduits	
5	Air outlet louvre	
6	Air inlet grille	